


Nurses' Station Standards	Preferred	Required*
Adjustable-height furniture	х	
If built-in (casework) work stations - Surface height should be 28.5" - 29" above finished floor at top of surface		х
Unit Clerk: 90 degree adjoining L-shape desk 6' x 8' x 2' (minimal requirement). For transaction counters that overhang on the clerical side; the depth for the height-adjustable flat panel monitor must be at least 24" from the end of the transaction counter nearest the employee, to the end of the desk.		х
Permanent Work Stations: Case worker, social worker - L-shape 4' x 2' x 2'	Х	
A. Desktop computer	х	
B. If laptop is used, ergonomics to approve laptop holder		х
Hoteling Work Stations: 2' x 2' minimum		х
Standing Work Stations/Countertops: Surface height should be 40"-41" above finished floor at top of surface, or height-adjustable		х
Work surfaces should have rounded edges, such as bullnose or radius		х
No under-desk (pencil) drawers at seated work stations, where the chair is positioned		х
Consider short distances for nursing to travel while designing the layout of the unit	Х	
Adjustable-height monitors and/or monitor arms		х
File drawer pedestals should be freestanding and mobile under desk	х	
Height-adjustable surface to accommodate shared equipment (printers, copiers, fax machines, scanners, etc.)	Х	
Toe-rest for standing work stations	х	
Soffit to reduce noise level. Soffit should drop down at least 12" and be at least 9"-12" wide.	х	
Install receptacles (e.g., electrical, data ports) 36" above the floor. Receptacles must be easily accessible to minimize bending.		x
Eliminate overhead bins	х	



For transaction counters that overhang on the clerical side, the depth for the height-adjustable flat panel monitor must be at least 24" from the end of the transaction counter nearest the employee to the end of the desk. (See Figure 1)



All Design and Construction projects should comply with any applicable Federal and/or State code, ADA requirements or any other requirement in order to accommodate conditions unique to the project. BJC Ergonomic Standards reflect the 5th-95th percentile population.

^{*}Requirement exceptions must be approved by BJC Ergonomics.